# N617CC

1980 Cessna 421C

# Airframe Logbook #5 of 5 2012 - 2022

Aircraft S/N: 421C-0897



Prepared by the worldwide aviation specialists at RidgeAire, Inc.



## AIRFRAME MAINTENANCE RECORDS

Registration No. NGITCC
Serial No. 4210-0897



# AIRFRAME MAINTENANCE RECORDS

Log No. \_5\_\_

Aircraft Registration No.	MEINGC
Model C-421C	
Serial No. 4216-089	77

CAHR AVIATION

### AHR AVIATION CRS#CF2R740R SAN ANTONIO INTERNATIONAL A/P (Airframe Entry) PG.1



N617CC

SN: 421C0897

WO# 37662

Hobbs: 6646.5

### PERFORMED THE FOLLOWING:

- Complied with AD 91-25-08 paragraph (a) fluorescent inspection was completed by Ruiz Testing Service [CRS RU7R547N] reference Report Number RTS-12-0378, paragraph (b) Installed Cessna Service Kit 421-142-1Spar Cap Support Installation at left wing position Paragraph (d) (1) left & right wing reinspect thereafter at intervals not to exceed 600-Hours TIS
- Serviced the nose and main gear tires in accordance with the Cessna Maintenance Manual Section 2-60.
- Serviced the oxygen system in accordance with the Cessna Maintenance Manual Section 2-60.
- Serviced the brake master cylinder with MtL-H-5606 in accordance with the Cessna Maintenance Manual Section 2-60.

All maintenance performed on this (Airframe, Engine, Propeller, Component) was performed in accordance with current regulations of the Federal Aviation Administration and was determined to be in an airworthy condition and is approved for return to service for work performed. Partinent details of the maintenance are on file at this Repair Station under the Work Order Number stated above. A copy of this work order has been given to the operator

INSPECTOR Jose Talamantes

DATE: 11/21/2012

AHR Aviation 367 Sandau Rd. San Antonio, TX 78216 Tel: (210) 377-3195

SAN ANTO (AIF N617CC	AMR AVIATION  ONIO INTERNATIONAL A/P  RFRAME) ENTRY PG.1  W/0#37719 HOBB: 6648.0  th Gildestope with test set functional good Checked and cleaned is good perform ILS chec with test set functional checked good LLLATION MANUAL P/N 190-00357-08 AUG. 2012.  The set of	
Inspector GILBERT A. TERRAZAS AHR Aviation	Date: 11/30/2012 567 Sandau Rd San Antonio, TX 78216 Tel: (210)377-3195	
	SUB-TOTALS this page  TOTALS—Carry forward to next page	

Caleb Haster A&P 2769663

maintenance manual, END

Boerne Stage Aero Service N617CC

Date: 02/12/2013

Airframe TT: 6675.8 Habbs: 6675.8

Reinstalled RH engine s/n 272484-R returned from Ram Aircraft for case change. See entries in engine log for all work performed. Installed using all existing accessories, mounts and hardware. Primed with oil per Ram instructions, checked fuel pressures IAW SID 97-3. C/W annual inspection IAW FAR 43 appendix (d) & Cessna service / maintenance manuals. Verified AD compliance done by A/P 2769663, bi weekly, per manufacture. A complete AD summery was furnished to aircraft owner and is part of aircraft permanent records. I certify that this airframe has been inspected in accordance with an annual inspection and was determined to be in an airworthy condition at this time. Charles Reynolds

A&P VA 521436738

1	i.		
		<u> </u>	
1			SUB-TOTALS this page

DATE	TOTAL TIME IN SERVICE	TOTAL THME SINCE OVERHAUL	TACH OR RECORDING METER TIME	DESCRI SIGNATURE & CERT	PTION OF WORK PERFORM TIFICATE NO. OF PERSON PERF	ED FORMING WORK		
HARAS.				TOTALS brought forward fr	TOTALS brought forward from previous page			
	AHR AVIATION	1	SAN AN	AVIATION CRS#CF2R740 TONIO INTERNATIONAL ne Entry) P	A/P G.1	P AVIATION ——		
NICAT	cc		SN: 4	121C0897 WO# 37953	Ho.	bbs: 6687.0		
N617 PERF	ORMED TH	E FOLLOV	VING:			-		
curren	Installed a Operation aintenance point regulations	an overhau hal check g erformed on of the Feder	led fuel pum ood with no this (Airfram al Aviation Ac	part number 2B7-29 serial r p part number 2B7-29 seri leaks noted. e, Engine, Propeller, Compo dministration and was determi ormed. Pertinent details of the above, A copy of this work o	nent) was performed in ac ned to be in an airworthy o	at this Repair		
Statio	The state of the s	19	1					
WICE	ECTOR J	co Talamar	ntes		DAT	E: 03/04/2013		
INSF	ECTOR	se raidinai	iios		San Anto	AHR Aviation 67 Sandau Rd. — onio, TX 78216 (210) 377-3195 —		
	1	1				-		
			4	McCREERY AVIATION CO., INC.		OBBS: 6721.9		
<del></del>	AIRFRAME 04/23/13 REG. NO.: N61			P.O. BOX 1659 McALLEN, TX 78505				
<u> </u>	04/23/13 REG. NO.: N61 MODEL: 421C			P.O. BOX 1659 McALLEN, TX 78505		·		
— — —	94/23/13 REG. NO.: N61 MODEL: 421C S/N: 0897  + COI OPI 13 C + COV + C/V	MPLIED WITH EN, NO META QUARTS OF A MPLIED WITH V DECAY TES V HEATER FU	L FOUND. INS EROSHELL WI H EXHAUST INS T CABIN HEAT EL SHUT OFF V	McALLEN, TX 78505 FER CHANGE. DRAINED ENGIN FALLED NEW OIL FILTERS P/N:	RAGRAPH (b)(c) AND (e). 101 REV. E. 18 A-107A.	=		

Page No.\_.

DATE TOTAL
TIME
IN
SERVICE

YOTAL TIME SINCE OVERHAUL TACH OR RECORDING METER TIME

DESCRIPTION OF WORK PERFORMED— SIGNATURE & CERTIFICATE NO. OF PERSON PERFORMING WORK



7929 Karl May Dr. Waco, Texas 76708 CRS No. AKoR541N Aircraft TT: <u>6775.9</u> Hour Meter: <u>6775.9</u> Date: <u>04/17/2014</u> Heater HM: <u>216.6</u>

### Cessna S/N 421C 0897 N617CC

On above referenced aircraft, removed inspection plates and panels for Annual Inspection. Checked pulleys, bellcranks, cables, and fairleads. Checked all flight controls for security and movement. Inspected all wing, tail, and landing gear attach points. Inspected all aircraft lighting and electrical. Ran gear retraction test per 421C Service Manual. Inspected wheels, tires, and brakes. Inspected fuel, hydraulic lines and fittings. Removed left engine and replaced rivets in beams as needed and installed new support cap, P/N 5054030-34S. Re-installed left engine and components. C/W A.D. 2000-01-16 per paragraphs (b), (c), (d), (e) and (g) re-certification of both engine entire exhaust systems. (See tags.) (Paragraph (g) next due at 04/2026 or 9275.9 Aircraft TT.) (Paragraph (b) next due at 6825.9 Aircraft HM.) Replaced left overboard exhaust support bracket. Repaired co-pilot's armrest. Serviced air conditioner system. Repaired crack in right horizontal trailing edge skin. Installed entry light properly. Installed new #5 seat location light switch. Installed placards for AFT cabin baggage shelves. Installed new left pilot's rudder pedal return spring. Installed (3) new bulbs for tell-tail lights. Troubleshot "EL" lights. Re-installed pilots defrost duct. Repaired wire for flap limit switch. Cleaned and treated flap wells. Installed new inboard flap panel attachment bushings. Installed new fuel filler cap "O' rings. Installed new fuel filler cap placards. Re-sealed fuel leak outboard lower wing. Installed new right main wheel half and new brake discs and pads linings for both mains. Installed new main fuel cap lanyards. Re-torqued right outboard flap bellcrank hardware and saftied. Installed right engine overhauled vacuum pump, P/N AA441CC, S/N 04W903. (See tag.) C/W MEB 00-4 per proper installation of lower rudder bearing attachment bracket and re-set travels per 421C service manual. Removed air conditioner inlet door and repaired bracket and re-installed components. Repaired crack in bulkhead AFT of air conditioner compartment. C/W A.D. 2004-25-16(R1) per MEB01-5 and Kelly Aerospace Power Systems S/B A-107-C. Installed new air conditioner hydraulie filter. Installed new main instrument air filter. C/W A.D. 95-09-13 per 600 hour inspection requirements. (Next due at 7375.9 HM.) Re-sealed both crossfeed fuel valves and ops checked good. Cleaned and treated in lower vertical access area. Cleaned and treated in AFT wheel well access panel areas. Re-scaled #10 fitting for right main aux pump. Cleaned in lower nose compartments. Manufactured and installed new forward nose gear uplock support channel. Installed main gear actuators wiring properly. Installed new ELT battery and tested unit per FAR 91.207 (d) requirements. (Battery next due replacement02/2016.) A.D.'s researched through bi-weekly 2014-06. See A.D. listing in log binder for all current and future compliance times. All above work done in accordance with Cessna 421C Service Manual and Air Impressions, Inc. 100 Hour/Annual Inspection Checklist. Aircraft approved for return to service. Pertinent details are on file under work order 3754.

Air Impressions, Inc. CRS# AK6R541N


	- Table 1
Air	IMPRESSIONS, INC.
Charge	TOTAL SERVICE STREET

7929 Karl May Dr. Waco, Texas 76708 CRS No. AK6R541N I certify this Aircraft has been inspected in accordance with a Annual Inspection and has been determined to be in an airworthy condition.

DATE 04/17/2014 HM 6775.9

AIRCRAFT TT 6775.9

WORK ORDER #3754 SIGNED

AIR IMPRESSIONS, INC REPAIR STATION # AK6R54IN

Page No. \_\_\_\_

DATÉ	TOTAL TIME IN SERVICE	TOTAL TIME SINCE OVERHAUL	TACH OR RECORDING METER TIME	DESCRIPTION OF WORK PERFORMED— SIGNATURE & CERTIFICATE NO. OF PERSON PERFORMING WORK
				TOTALS brought forward from previous page



7929 Karl May Dr. Waco, Texas 76708 CRS No. AK6R541N

### Aircraft TT: 6978.4 Hour Meter: 6978.4 Date: 03/20/2015 Heater HM: 278.3

### Cessna S/N 421C 0397 N617CC

On above referenced aircraft, removed inspection plates and panels for Annual Inspection. Checked pulleys, bellcranks, cables, and fairleads. Checked all flight controls for security and movement. Inspected all wing, tail, and landing gear attach points. Inspected all aircraft lighting and electrical. Ran gear retraction test per 421C Service Manual. Inspected wheels, tires, and brakes. Inspected fuel, hydraulic lines and fittings. Installed new EGT gauge, P/N 46158, S/N 266259. Installed overhauled attitude gyro in co-pilot's position, P/N 102-0041-04, S/N 214L336G. (See tag.) Installed new instrument air filter, P/N AM1035351A. Checked autopilot pitch servo cable tensions. Installed new springs for APU receptacle access door. Installed fiberglass hubcaps per STC SA02430LA. (See 337.) Installed external AFT body strakes per STC SA01935LA and 8110-3 dated 11/7/2013. (See 337). New aircraft weight and balance computed. Installed new circuit breakers for starter, right engine gage, turn and bank, and left wing baggage light. Troubleshot and repaired cabin light system short in electrical. Installed new overhauled left fuel selector, P/N 9910201-1, S/N 5974. Re-sealed both main gear uplock actuators. Installed new fuel cap "O" rings. Installed new center forward pressure drain seal, CM3575-4. Rigged nose steering cables per Service Manual. Removed left elevator and installed new bearings, P/N MS24462-4. Re-sealed both master cylinders and parking brake valve. Serviced air conditioning system. C/W A.D. 2004-21-05 per inspection and test of heater assembly. (Next due 03/2017 or 378.3 Heater HM.) C/W A.D. 2004-25-16(R1) per MEB01-5 and Kelly Aerospace Power Systems S/B A-107-C. (Next due at 7078.4 HM.) Treated inboard wing access panel areas Re-sealed left fuel crossfeed shut-off valve. Treated pressure bulkhead in nose compartment. Re-scaled fitting for landing gear sequence valve. Replaced pilot's right ruider pedal roll pin. Troubleshot and repaired horizontal surface boots activation. C/W A.D. 2000-01-16 per paragraphs (b), (c), and (e). (Paragraph (b) next due at 7028.4 HM.) C/W A.D. 84-26-02 per installation of new induction air filters. (Next due at 7278.4 HM.) ELT battery unit tested per FAR 91.207 (d) requirements. (Next due at 03/2016.) A.D.'s researched through bi-weekly 2015-05. See A.D. listing in log binder for all current and future compliance times. All above work done in accordance with Cessna 421C Service Manual and Air Impressions, Inc. 100 Hour/Annual Inspection Checklist. Aircraft approved for return to service. Pertinent details are on file under work order 3963.

Air Improssions, Inc. CRS# AK6R541N

AIR IMPRESSIONS, INC.  7929 Karl May Dr. Waco, Texas 76708 CRS No. AK6R541N  DATE 03/20/2015 HM 6978.4  AIRCRAFT TT 6978.4  WORK ORDER #3965 SIGNED  AIR IMPRESSIONS, INC REPAIR STATION # AK6R541N	
---	--

No	TOTAL TIME IN SERVICE	TOTAL TIME SINCE OVERHAUL	TACH OR RECORDING METER TIME	DESCRIPTION OF WORK PERFORMED— SIGNATURE & CERTIFICATE NO. OF PERSON PERFORMING W	ORK
21 mg/5 file	<b>Q</b> ETTION	V-2		TOTALS brought forward from previous page	
	R&I Wor THE REP	RK PERFORM Instruments a k accomplishe k Order refere AIRCRAFT C AIRCRAFT C AIRED AND I	MED:  nd transponder  ed referenced to  ince WQ731  DR APPLIANCE NSPECTED IN  ON REGULATO	TIME AEROSPACE LLC PO Box 521 Schertz, Texas 78154  LOG BOOK ENTRY  Reg.#: N871GC  Model: 421C S/N: 421C0897  r for access to testing and serial numbers o Manufactures Manuals.  E(S) IDENTIFIED ABOVE WAS I ACCORDANCE WITH CURRENT IONS AND WAS FOUND AIRWORTHY TH RESPECT TO WORK PERFORMED  TECHNICIAN - Dean DelValle Lic. # A3591172	
		# te A A Irr W C C C T	certify that the equired by FAI accordance of accordance of the easted on date. It is a continued on the easted on date. It is a continued on the easted on the east on the easted on the east of the easted on the	WO# ACTIVITIES OF ACTIVITIES O	

TOTALS-Carry forward to next page



7929 Karl May Dr Wares Texas 76768 CRS No. AK5R5 HN Aircroft TT:: 7122.7 Hour Meter: 7122.7 Date: 04/14/2016 Heater HM: 314.5

### Cessna S/N 421C 0897 N617CC

On above referenced aircraft, removed inspection plates and panels for Annual inspection. Checked pulleys, belieranks, cables, and fairleads. Checked all flight controls for security and movement. Inspected all wing, tail, and landing gear attach points. Inspected all aircraft lighting and electrical. Ran gear retraction test per 421C Service Manual. Inspected wheels, tires, and brakes. Inspected fuel, hydraulic lines and fittings. Re-scaled lower cabin entry door snubber and serviced. Adjusted left throttle warning switch per Service Manual. Repaired and re-installed pilots defrost duct outlet at glare shield. Installed new alternate air cable knob P/N CPN 167. (See 3130-3.) Installed new lamp P/N DA-27 for right tail field light and operational tested. Installed new chafe tape on underside of spoiler panels. Removed right aileron and lubricated yoke bearings, re-torqued yoke assembly and re-installed aileron per Service Manual. Installed new fuel cap "O" rings. Installed new cannon plug for right tach generator. (See 8130-3 forms.) Repaired broken wire for left engine RAM EGT probe and installed new probe P/N 2871, installed new right engine #1 EGT probe P/N M-111. (See 8130-3.) Installed overhauled co-pilot horizon gyro P/N 102-0041-04 S/N A82-0021. (See 8130-3.) Removed and re-installed oxygen hottle after hydrostatic testing, next due 04/2019 (3 year bottle.) Installed new EUT battery and tested unit per FAR 91.207 (d) requirements. (Battery next due 04/2018.) Installed new main aircraft hydraulic filters and air conditioner hydraulic filter, next due in 400 hours. C/W A.D. 2004-25-16(R1) per inspection of heater fuel regulator shut-off valve with no defects noted, due each 100 hours or annual.) C/W A.D. 2000-01-16 per paragraphs (b), (c), (d) and (e) inspections. (Paragraph (b) next compliance due in 50 hours or 30 days whichever is later.) Installed new heater plenum duct in nose of aircraft, P/N CM3211-18A4.2. (See 8130-3.) Instailed new chafe strip on nose gear door actuating bar, De-fueled left fuel tank and removed and replaced crossfeed fuel valve after installing new "O" ring. Installed all new left and right main brake pad linings. Repaired negative cable end at main battery. C/W A.D. 2016-07-24 per replacement of all elevator trim tab link rod hardware with new per Cessna MEB 27-02. Installed new P/N CM3211-10B38.0 duet in right wing stub. Installed new AE3663162J0170 hose from right oil filter to oil pump. A.D.'s researched through bi-weekly 2016-06. See A.D. listing in log binder for all current and future compliance times. All above work done in accordance with Cessna 421C Service Manual and Air Impressions, Inc. 100 Hour/Annual Inspection Checklist. Aircraft approved for return to service. Pertinent details are on file under work order 4258.

Air impressions, Inc. CRS# AK6R341N

Air Impressions, Inc. 7929 Karl May De, Word, Texas 76708 CRS No. AkbR541N	I certify this Aircraft has been inspected in accordance with a Annual inspection and has been determined to be in an airworthy condition.  DATE 04/14/2016 HM 7122.7  AIRCRAFT TT 7122.7  WORK ORDER #4258  SIGNED AIR IMPRESSIONS, INC  REPAIR STATION # AK6R541N	
	SUB-TOTALS this page	

Page No.:

DATE

TOTAL TIME IN SERVICE TOTAL TIME SINCE OVERHAUL TACH OR RECORDING METER TIME



7929 Karl May De Waco, Texas 76708 CRS No. AK6R5418 Aircraft TT: 7247.7 Hour Meter: 7247.2 Date: 05/10/2017 Heater HM: 350.7

### Cessna S/N 421C 0897 N617CC

On above referenced aircraft, removed inspection plates and panels for Annual Inspection. Checked pulleys, belleranks, cables, and fairleads. Checked all flight controls for security and movement. Inspected all wing, tail, and landing gear attach points. Inspected all aircraft lighting and electrical. Ran gear retraction test per 421C Service Manual. Inspected wheels, tires, and brakes, Inspected firel. hydraulic lines and fittings. C/W A.D. 2000-01-16 per paragraphs (b), (c) and (e) inspections. (Paragraph (b) next due 7297.7 HM.) C/W A.D. 84-26-02 per installation of new induction air filters. (Next due at 7547.7 HM.) Installed overhauted vacuum pumps on both engines, P/N 441CC, S/N OC8002 and OC8003. Troubleshot air conditioner system and installed new compressor, P/N 58033 and serviced system. Installed new right prop cable, P/N 1220-42. (FAA/PMA.) Troubleshot prop de-ice and installed new brush assemblies, P/N B40189 on right side. Installed compass seal kit. Installed new cabin fire extinguisher. Installed new air vent louvers at #3 seat location. Installed new right landing light bulb. Installed new right nav. light bulb. Installed new tail light bulb. Installed new right AFT tell tail light bulb. Installed new rivets as needed for lower wing to fuselage skins. Cleaned exhaust trails. Installed overhauled tachometer, P/N C668016-0108RX, S/N 03F116. (See tag.) C/W A.D. 91-25-08(R1) per inspection of wing front spar upper caps. (Next due at 7847.7 HM or 7847.7 Aircraft TT.) C/W A.D 95-09-13 per inspection and test of fuel inlet float valves. (Next due at 7847.7 HM or 7847.7 Aircraft TT.) C/W A.D. 2004-21-05 per inspection and test of heater assembly. (Next due at 450.7 or 05/2019.) C.W A.D. 2004-25-16(R1) per MEBD1-5 and Kelly Aerospace Power Systems S/B A-107C. (Next due at 7347.7 HM.) Installed new ELT battery and tested unit per FAR 91.207 (d) requirements. (Battery next due 03/2019.) Nitrogen bottle hydrostatic tested this date, re-installed and serviced and ops cheeked. Installed new main aircraft battery, P/N G-246, S/N G02956757. Installed new ramp assembly, P/N 5742204-2 for nose gear. Re-installed pilots defrost duct properly. Installed new battery cable insulator grommets. C/W A.D. 2016-17-08 per inspection of elevator trim tab hardware. (Next due at 7357.7 HM or 05/2018.) Installed new outer bearing and race for right main wheel. Installed new nose wheel bearings and races. A.D.'s researched through bi-weekly 2017-09. See A.D. listing in log binder for all current and future compliance times. All above work done in accordance with Cessna 421C Service Manual and Air Impressions, Inc. 100 Hour/Annual Inspection Checklist. Aircraft approach for return to service. Pertinent details are on file under work order 4469.

Air Impress pers, Inc. CRS# AK6R541N I certify this Aircraft AIR IMPRESSIONS INC inspected in accordance with a Annual 7929 Karl May Da Inspection and has been determined Wago, Texas 76708 to be in an airworthy condition. CRS NovAK6R541N 7247.7 HMDATE 05/10/2017 7247.7 AIRCRAFT TT WORK ORDER # SIGNED AIR IMPRESSIONS, INC REPAIR STATION # AK6R541N

Page No. \_\_\_\_ TACH OR RECORDING METER TIME TOTAL TIME IN SERVICE TOTAL TIME SINCE OVERHAUL DESCRIPTION OF WORK PERFORMED-SIGNATURE & CERTIFICATE NO. OF PERSON PERFORMING WORK DATE TOTALS brought forward from previous page IAT:

JALL	McGregor Executive Airport McGregor	DI 1X.100D)	
Rog. #: N627CC Date: 19/May/201 Make: Cessna Model: 42	LB CRS # 2JVR917C 21C Serial #: 421C0597	Work Order 5: 18-0224 TT: 7297.3	
certify that the altimeter and matte system tests required 1	by 14 CFP, part 91; 91 411 and transponder tests golder 91 41 clustered and found to comply with 14 CFR part 41, appendicts	[3, including data correspondence, required by $g \in E$ and $F$	
	1855 Egcoder #1 Model EA 80	01A Serial No3855	
	Encader #1 MadelN/A	A Serial No N/A	7
Transponder #I Model GTX 330 Sectal No			_
Transponder #2 Model <u>GTX 327</u> Smial No			
The altimeter was rested to NK feet on IS May 2			8
The transponder was tested on			
Static system leak tested to _15K' _cs; _18 MA Stenature Report Billingsles; Repairmans Conficant # 241342c	AY 2014		

### Altimeter Certification Form JAG Aviation, Inc. 357 McGregor Airport Rd McGregor, Tr. 76657 CRS# 2JVR917C

Altimeter Part Number: (66/014 - 0/0) (5934PA-1)	Encoder Part Number:
Altimeter Serial Number:	Encoder Serial Number:
Service Order Number: 18-0224	Aircraft Model: 421 C
Aircraft ID Number: NU17CC	Aircraft Tach/Hobbs: Total:

	Pressure	Difference	Tolerance	Reading		
	28.10	-1,727	25	-1720	Hysteresis 50% 75'	+10
	28.50	-1,340	25	-1330	Hysteresis 40% 75'	+20
	29.00	-863	25	-860	After Effect Test 30'	+20
	29.50	-392	25	- 390	Baro. Beginning	29.82
60	29.92	0	0	Δ	Baro. Ending	29.83
	30.50	+531	25	+540	Baro Reading Start	570
E	30.90	+893	25	+900	Baro Reading End	590
	30.99	+974	25	1980		- //

	Accura	acy	Frie	tion
Pressure	ToL	Reading	ToL	
-1000	20	-1000	I	
0	20	0		
500	20	500		
1000	20	1010	70	20
1500	25	1510		
2000	30	2000	70	20
3000	30	3000	70	20
4000	35	4000	_	
5000			70	40
6000	40	6010	_	
8000	60	8030		
19,000	80	10040	80	40
.2,000	90	12050		
14,000	100	14060		
15,000			90	30
16,000	110	16060		
18,000	120	18070	Leak	10
20,000	130	20096	100	30
22,000	140	22090		
25,000	155	25/00	120	80
30,000	180	30080	140	100
35,000	205		160	. /
40,000	230	13/2	180	المراد
45,000	255	1		7
50,000	280		250 4	

Technician: My Mu

Inspector:

Date: 18- May - 2018

### Altimeter Certification Form JAG Aviation, Inc. 357 McGregor Airport Rd McGregor, Tx. 76657 CRS# 2JVR917C

Altimeter Part Number: EA80/A	Encoder Part Number: EA 801A
Altimeter Serial Number: 3855	Encoder Serial Number: 3755
Service Order Number: 18-0324	Aircraft Model: 421C
Aircraft ID Number: N617CC	Aircraft Tach/Hobber Total

Pressure	Difference	Tolerance	Reading		
28.10	-1,727	25	17/7	Hysteresis 50% 75'	+5
28.50	-1,340	25	1537	Hysteresis 40% 75'	-20
29.00	-863	25	857	After Effect Test 30'	+15
29.50	-392	25	377	Baro, Beginning	21.86
29.92	0	0	0	Baro. Ending	24.83
30.50	+531	25	543	Baro Reading Start	530
30.90	+893	25	403	Baro Reading End	545
30.99	+974	25	983		

	Accura	acy	Fric	tion	
Pressure	Tol	Reading	ToL	Reading	
-1000	20 .	-480			]
0	20	<b>#</b> 5			1
500	20	500			1
1000	20	(000)	170	0	
1500	25	1515			
2000	30	2020	70	0	
3000	30	3020	70	0	1
4000	35	4030			
5000		1	70	0	1
6000	40	5,935			±3
8000	60	8000			+5
10,000	80	10,070	80	0	+70
12,000	90	12.850			1 ,.
14,000	100	14,045	(6)		
15,000			90	0	ĺ
16,000	110	16,080-			
18,000	120	18,070	Leak	60	
20,000	130	20,078	100	0	
22,000	140	22/110			
25,000	155	25.060	120	0	Ì
30,000	180	30,060	140	<b>6</b>	
35,000	205		160		
40,000	230		180		
45,000	255				
50,000	280		250		

Technician: mil mult

Inspector:

xy they

Date: 19 Mp 7 7018

### TRANSPONDER CERTIFICATION FORM

W.O. No.:	18-0224 Customer:		N No.:	NGITCC	Date:		
TXP # 1	Mfg: Gamin	Model.: GTX-330	Part No:		Serial No:	8414057	4
TXP # 2	Mfg.: Gormin	Model.: <u>G7x-327</u>	Part No:_		Serial No:	837-1151	4
	Performing:						
Certification				.5			
	REPLY FREQUENCY			SU	JPPRESSIO	ON (%)	
ATCODEC	#1	#2		012 ( 43	.67.3	0.0.4.0	2007
ATCRBS (	[090+7-3]	1088.6		0db(<1 #1	%) #2	-9db ( >9 #1	/0%) #2
1B, 2B, 3B				#1	112	T T	
Mode S (10	90+/-3)			0%	0%	10%	75%
1A, 2A, 3A				- 70	- / -	11-7-	
Mode S (10	11000			RF PEA	к ойтри	T POWER (w	ratts)
						#1	#2
	RECEIVER SENSE.(-dt	bm)		(Class $B = 7$ )	0 - 500w)	225	
	#1	#2		1B, 2B ATC		#	145
ATCRBS (-	73+/-4 )	7.1	*	1B, 2B, 3B N	Mode S	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
		-71		(Class A = I.	25 - 500w)		
Mode S (-7-	4+/-3 )			1A, 2A ATO			
	-74			1A, 2A, 3A,	4 Mode S	162 E 113	Car F.
Mode 3/A &	1 - 0	-0					
Difference (	< 1db)				de S ADDI	RESS	
	Made of DD Contractor			( Address use	∌d	)	
	Mode S DIVERSITY TR			~		#1	#2
	(Chan. Isolation > 20db	•		Correct		V	一 其中企业9
Selected Ant	#1	#2		Incorrect		V	Lu - 289 (b)
Non-Selecte		100 C		Incorrect		で語る。	EN NOW
Non-Selecte	a Ant.	1201 L1					
				Мо	de S ALL-(		40
	Mode S FORMATS			Made Caste	A 11 C-11	#1	#2
	#1	#2		Mode S only		-	32.5
UF-4 Altitud		72		ATCRBS / S		Vy	
ATCRBS 'C'	-	34752		ATCRBS on	іу Ап-Сап	1	
UF-5 LD.		200			azat dimenan		
ATCRB\$ 3/4	(200.:	2M 24.5		;	SQUITTER		***
ATCKD\$ 50	A I.D. (700	10 - 25 '				#1	#2
				Mode S (1 / s	sec.)	890AS	XX TO LAW.
			7-3	7	•	18-M44	1- 2018
Teanenanda	Certification Form	1	/	10			2010
ransponder Rev:	Certification Form	Authorized S		De watermara	a	Date	
IXGY,		ior jag Avia	suon inc C	RS # 2JVR917	C		

Page	Nο	

DATE	TOTAL TIME IN SERVICE	TOTAL TIME SINCE OVERHAUL	TACH DA RECORDING METER TIME	DESCRIPTION OF WORK PERFORMED— SIGNATURE & CERTIFICATE NO, OF PERSON PERFORMING WORK
				TOTALS brought forward from previous page



7929 Karl May Dr. Wace, Texas 76708 CRS NovaK6R541N


### Aircraft TT: 7297.3 Hour Meter: 7297.3 Date: 06/01/2018 Heater HM: 359.1

### Cessna S/N 421C 0897 N617CC

On above referenced aircraft, removed inspection plates and panels for Annual Inspection. Checked pulleys, belleranks, cables, and fairleads. Checked all flight controls for security and movement. Inspected all wing, tail, and landing gear attach points. Inspected all aircraft lighting and electrical. Ran gear retraction test per 421C Service Manual. Inspected wheels, tires, and brakes. Inspected fuel, hydraulic lines and fittings. C/W A.D. 2000-01-16 per paragraphs (b), (c), (d) and (e) inspections. (Paragraph (b) next due 7347.3 HM.) Installed new left exhaust bypass elbow, P/N A9910300-03. Installed new left exhaust tailpipe, P/N K9910300-01. Installed new right throttle cable, P/N 9910272-28. Cleaned and lubed alternate air cables and housings. Installed new re-furbished EL panel lights, P/N's 9910077-35 and -36 and 9910122-6. (See tags.) Replaced rivets as needed for lower left and right wing skins and skins to fuselage. Installed new rod ends for both main gear door linkage. Replaced several cowling fasteners. Replaced two cowling oil access panel latch assemblies. Installed new fuel filler cap "O" rings. Install all new tires. Installed overhauled nose gear actuator, P/N 9910139-9, S/N AI2213. Installed overhauled right aileron, P/N 5124000-98, S/N 105. Painted and balanced. Installed new bearings at right outboard flap-inboard attachment points. Installed overhauled co-pilot's D.G., P/N 1U262-001-39 400B-30, S/N T28117E. Replaced both top cowl do-nut seals. Re-positioned air conditioner compartment inlet air door as to close properly. C.W A.D. 2004-25-16(R1) per MEB01-5. (Next due at 7397.3 HM.) C/W A.D 2016-17-08 per inspection/replacement of elevator trim tab hardware. (Next due at 7407.3 HM.) Installed new nose wheel bearings and races. Installed overhauled left main gear actuator, P/N 9910136-10, S/N 3265. ELT unit tested per FAR 91.207 (d) requirements. (Battery next due 03/2019.) A.D.'s researched through bi-weekly 2018-09. See A.D. listing in log binder for all current and future compliance times. All above work done in accordance with Cessna 421C Service Manual and Air Impressions, Inc. 100 Hour/Annual Inspection Checklist. Aircraft approved for return to service. Pertinent details are on file under work order 4655.

Air Impressions, Inc.

AIR IMPRESSIONS, INC.  7929 Karl May Dr.  Waco, Texas 76708  CRS No. AK6R541N	I certify this Aircraft has been inspected in accordance with a Annual Inspection and has been determined to be in an airworthy condition.  DATE 06/01/2018 HM 7297.3  AIRCRAFT TT 7297.3  WORK ORDER #4655  SIGNED AIR IMPRESSIONS, INC  REPAIR STATION # AK6R541N
=	



SEPTYTCE	TOTAL	TACH OR RECORDING	DESCRIPTION OF WORK PERFORMED.	
-	OVERHALL	METER TIME	SIGNATURE & CERTIFICATE NO. OF PERSON PERFORUSING WORK	
			TOTALS brought forward from previous page	
		1		7
	Am Sumen	Stages Me	I certify this Aircraft has been	
	PARTITION AND ADDRESS OF	AUTO BARRETS	inspected in accordance with a Annual	
100		Karl May Dr. Texas 76708	Inspection and has been determined to be in an airwarthy condition.	
		o. AK6R541N	DATE_11/07/2019 HM 7337,3	
			AIRCRAFF TI 7337.3	-
			WORK ORDER #4966 SIGNED	
200			AIR IMPRESSIONS, INC	
			REPAIR STATION # AK6R54IN	
1315				
				1000
		OZARK AT	RCRAFT MAINTENANCE LLC	-
		OZARK AL	RCRAFT MAINTENANCE LLC	-
February 26	, 2021_CESS	CAP DNA 421C - 87	TORMANDEAU RIGIONAL ARMOND CAPE GIRANDEAU MO 6070)	-
10005 7514	. I Otal him	GAP DNA 421C S/ Se 7514 1	N GRANDEAU REGIONAL AMPONT CAPE GIRANDEAU MO 6770) N 421C0897 N617CC	=
Hoods 7514 Da this date	I Total tim	CO INA 421C S/ in 7514.) Append inco-	N GRANDEAU REGIONAL AMPONO CAPE GIRANDEAU MO 6570) N 421C0897 N617CC	-
noos 7514 Da this date and perform with and hi	I fotal tim completed an ed the following rdmuhe system	COP SNA 421C S/ sc 7514.) Annual inspec- og work. Jack	CAPE GRANDEAU ANGIONAL AMPORT CAPE GRANDEAU AND 6700) N 421C0897 N617CC  Rico IAW FAR 43 (App d) and lubricated IAW service manual ed assuraft. Serviced blow down bottle with nitrogen. Service	-
Hoods 7514 Do this date and perform while and his enemies and	I Total tim completed an ed the follows drauhe system I mees, Service	CAP  ENA 421C S/  E 7514.]  Annual inspecting work. Jack  no replaced by	CAPE GRANDEAU AND GOOD  N 421C0897 N617CC  Sixon IAW FAR 43 (App. d) and labricated IAW service manual agreement. Serviced blow down bottle with aitrogen. Service drawlic filters. Packed all wheel bearings and replaced nose wheel	
Do this date and perform wake and by comings and form tacks	I Total tim completed an ed the following rebushe system I races. Service Installed new	ONA 421C S/ to 7514.1 Annual inspec- og work. Jack no replaced by ed nose strut.	CAPE GRAPDEAU MO 6700 N 421C0897 N617CC Sixon IAW FAR 43 (App. d) and lubricated IAW service manual ed asceraft. Serviced blow down bottle with mitrogen. Service drawlic filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed aircraft	-
Hoose /514 Do this date and perform while and hy entings and from jacks.	I Total tim completed an ed the followi rebuthe system Installed new (c) no defect	NA 421C S/ to 7514.1 Annual inspec- ag work. Jack no replaced by ed nose strut.	CAPE GRAPDEAU MO 6700) N 421C0897 N617CC  Stion IAW FAR 43 (App d) and Inbricated IAW service manual ed asterult. Serviced blow down bottle with nitrogen. Service draube filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft dor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW	
Hoose 7514 On this date and perform whice and in contract and	omposted an ed the following drauhe system lessalled new (c) no defect by 2022. Insparation of the following system.	NA 421C 5/ is 7514.) Annual inspecting week. Jack ins replaced by ed nose simil viscount regula s noted. Para sected ELT IA	CAPE GRAPHER VAIO 6770) N 421C0897 N617CC  Sicon IAW FAR 43 (App d) and labricated IAW service manual sed asceraft. Serviced blow down bottle with nitrogen. Service draube filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Respond aircraft stor filters P/N B3-5-9. CW AD2000-01-36 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.	
Do this date and perform whice and hy- rentings and remains and the period and the period and the period and the period of the p	omposted an ed the following draube system linears. Service lustabled new (c) no defect system. AD2 27-02 Meeting.	NA 421C S/ to 7514.) Annual inspense work. Jack ne replaced by ed nose strin, vector, Para- tected ELT IA 2016-07-24 no	CAPE GRAPHEAU AND GENT (ASPECT  Sion IAW FAR 43 (App d) and labricated IAW service manual red asceraft. Serviced blow down bottle with aitrogen. Service draube filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed aircraft filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at holdes 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 each inspection due February 2022.  4-26-16 by inspection of elevator trim tab actuality attachment.	
Do this date and perform whice end by comings and from jacks. Here (b), (c), quant Februs (sevend O).  AW MEB:	omposted an ed the following draube system literatures. Service literatures in the following draubes. Service literatures in defect by 2022. Insp. system. AD2 17-02. Next in a and tested.	NA 421C 5/ to 7514.) Annual inspense work. Jack ne replaced by ed nose strut. vectum regula s noted. Para- tected ELT IA 1016-07-24 nov	CAPE GRAPHEAU ARCHOPAL ARROWS  N 421C0897 N617CC  Rich IAW FAR 43 (App d) and labricated IAW service manual ed around. Serviced blow down bottle with nitrogen. Service draube filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed aircraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91.207 (d) 1-4 eaxt inspection due February 2022.  4-26-16 by inspection of elevator trim tab actuator attachment application before 2711.2. Blow out right and left manufold.	
Do this date and perform whice end by comings and from jacks. The performance of the perf	orespected an ed the following draube system lessalled new (c) no defect my 2022. Inspections, AD2 17-02. Next in a and tested.	NA 421C 5/ is 7514.] Annual inspense work. Jack ins replaced by ed nose strut. vacuum reguli s noted. Para- scoted ELT IA 2016-07-24 nov ispection due.	CAPE GRANDEAU AND GYM) N 421C0897 N617CC  Stice IAW FAR 43 (App d) and labricated IAW service manual red asceraft. Serviced blow down bottle with nitrogen. Service draube filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft after filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022. 4-25-16 by inspection of elevator trim tab actuator attachment light 2021 or hobbs 2711.2. Blow out right and left manifold authore indictor on left instrument panal 202102.	
Do this date and perform white and perform white and its committee and its committee packs. Our a (b), (c), spain February and MEB-1 wessure line NN 220M22 assument a constitution that	omposted an ed the following draube system lesses. Service Installed new (c) no defect system. AD2 17-02. Next in a and tested. 1863. Replaces it filter P/N A	CAP  ENA 421C S/  E 7514.]  Annual inspecting work. Jack  The replaced hy  ed nose strut.  vacuum regula  s noted. Para  ecoted ELT IA  2016-07-24 rev  aspection due s  hatalled overh  f attach region  MICUSSSIA. 1	CAPE GRANDEAU ARCHONAL ARRONG  CAPE GRANDEAU ARCHONG  N 421C0897 N617CC  Sixon IAW FAR 43 (App d) and labricated IAW service manual sed ascendt. Serviced blow down bottle with nitrogen. Service drauble filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.  4-25-16 by inspection of elevator trim tab actuator attachment and attachment indicator on left instrument panel P/N102-004 I de pilot armiest. Replaced bonding strap to midder. Installed new Replaced instrument panel P/N102-004 II.	
Hoose 7514 On this date and perform bruke and ky beerings and from packs, para (b), (c), again February MEB, wessure line SN 220M2; ascrument a certally that wen imposes	omposted an ed the following draube system (c) no defect by 2022. Insparation of the following the f	NA 421C 5/ iz 7514.) Annual inspecting replaced by ed nose similar regular sucted. Para- sected ELT IA 2016-07-24 revisioned overhilastalled overhilastalled overhilastalled overhilastalled installed install	CAPE GRANDEAU ARCHONAL ARRONG  CAPE GRANDEAU ARCHONG  N 421C0897 N617CC  Sixon IAW FAR 43 (App d) and labricated IAW service manual sed ascendt. Serviced blow down bottle with nitrogen. Service drauble filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.  4-25-16 by inspection of elevator trim tab actuator attachment and attachment indicator on left instrument panel P/N102-004 I de pilot armiest. Replaced bonding strap to midder. Installed new Replaced instrument panel P/N102-004 II.	
On this date and perform brake and by form packs. page 104, (c), again Februar Serviced Of IAW MED-1 pressure line SW 220M22 ascrument a county that were inspect on greation against a serviced or a	omposted an ad the following draube system in the following draube system in the following draw following the following draw following the following draw following the following draw following the following the following draw following draw draw draw following the following draw draw draw draw draw draw draw draw	NA 421C S/ iz 7514.) Annual inspense work Jack ne replaced by ed nose strut, vacuum reguli s noted. Para- rected ELT IA 2016-07-24 nov inspection due, lastalled overhit stack rest on MIOJS35IA. () as 43 App (d) an	CAPE GRANDEAU ARCHONAL ARRONG  CAPE GRANDEAU ARCHONG  N 421C0897 N617CC  Sixon IAW FAR 43 (App d) and labricated IAW service manual sed ascendt. Serviced blow down bottle with nitrogen. Service drauble filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.  4-25-16 by inspection of elevator trim tab actuator attachment and attachment indicator on left instrument panel P/N102-004 I de pilot armiest. Replaced bonding strap to midder. Installed new Replaced instrument panel P/N102-004 II.	
On this date and performs bruke and by forms packs. page (b), (c), spain Februs Serviced O. A. M.E.B.: pressure line SN 230M2: assument a contrly that were inspect negotion as and airwood ai	omposted an ed the following draube system lessabled new (s) no defect by 2022. Insparations. AD2 17-02. Next in a and tested in filter P/N Al this aircraft in ed IAW FAR ed was determined to condition.	NA 421C S/ iz 7514.) Annual inspense work Jack ne replaced by ed nose strut, vacuum reguli s noted. Para- rected ELT IA 2016-07-24 nov inspection due, lastalled overhit stack rest on MIOJS35IA. () as 43 App (d) an	CAPE GRANDEAU ARCHONAL ARRONG  CAPE GRANDEAU ARCHONG  N 421C0897 N617CC  Sixon IAW FAR 43 (App d) and labricated IAW service manual sed ascendt. Serviced blow down bottle with nitrogen. Service drauble filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.  4-25-16 by inspection of elevator trim tab actuator attachment and attachment indicator on left instrument panel P/N102-004 I de pilot armiest. Replaced bonding strap to midder. Installed new Replaced instrument panel P/N102-004 II.	
On this date and performs tracks and performs tracks are from packs. Person forms from February and MEB 200M2: AW MEB 200M2: ASSET TO THE TRACKS AND THE TRA	omposted an od the following draube system installed new (s) no defect by 2022. Insparations. AD2 17-02. Next in and tested in filter P/N Al this aircraft in od IAW FAR and was determined was determined to condition.	NA 421C S/ iz 7514.) Annual inspense work Jack ne replaced by ed nose strut, vacuum reguli s noted. Para- rected ELT IA 2016-07-24 nov inspection due, lastalled overhit stack rest on MIOJS35IA. () as 43 App (d) an	CAPE GRANDEAU ARCHONAL ARRONG  CAPE GRANDEAU ARCHONG  N 421C0897 N617CC  Sixon IAW FAR 43 (App d) and labricated IAW service manual sed ascendt. Serviced blow down bottle with nitrogen. Service drauble filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.  4-25-16 by inspection of elevator trim tab actuator attachment and attachment indicator on left instrument panel P/N102-004 I de pilot armiest. Replaced bonding strap to midder. Installed new Replaced instrument panel P/N102-004 II.	
On this date and performs tracks and performs tracks. Page 10 (c), (c), apair Februs 50 MEB 200 MEB 20	omposted an od the following draube system installed new (s) no defect by 2022. Insparations. AD2 17-02. Next in and tested in filter P/N Al this aircraft in od IAW FAR and was determined was determined to condition.	NA 421C S/ iz 7514.) Annual inspense work Jack ne replaced by ed nose strut, vacuum reguli s noted. Para- rected ELT IA 2016-07-24 nov inspection due, lastalled overhit stack rest on MIOJS35IA. () as 43 App (d) an	CAPE GRANDEAU ARCHONAL ARRONG  CAPE GRANDEAU ARCHONG  N 421C0897 N617CC  Sixon IAW FAR 43 (App d) and labricated IAW service manual sed ascendt. Serviced blow down bottle with nitrogen. Service drauble filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.  4-25-16 by inspection of elevator trim tab actuator attachment and attachment indicator on left instrument panel P/N102-004 I de pilot armiest. Replaced bonding strap to midder. Installed new Replaced instrument panel P/N102-004 II.	
On this date and performs tracks and performs tracks are from packs. Person forms from February and MEB 200M2: AW MEB 200M2: ASSET TO THE TRACKS AND THE TRA	omposted an od the following draube system installed new (s) no defect by 2022. Insparations. AD2 17-02. Next in and tested in filter P/N Al this aircraft in od IAW FAR and was determined was determined to condition.	NA 421C S/ iz 7514.) Annual inspense work Jack ne replaced by ed nose strut, vacuum reguli s noted. Para- rected ELT IA 2016-07-24 nov inspection due, lastalled overhit stack rest on MIOJS35IA. () as 43 App (d) an	CAPE GRANDEAU ARCHONAL ARRONG  CAPE GRANDEAU ARCHONG  N 421C0897 N617CC  Sixon IAW FAR 43 (App d) and labricated IAW service manual sed ascendt. Serviced blow down bottle with nitrogen. Service drauble filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.  4-25-16 by inspection of elevator trim tab actuator attachment and attachment indicator on left instrument panel P/N102-004 I de pilot armiest. Replaced bonding strap to midder. Installed new Replaced instrument panel P/N102-004 II.	
Do this date and perform the eading and performance and in the case of the cas	omposted an od the following draube system installed new (s) no defect by 2022. Insparations. AD2 17-02. Next in and tested in filter P/N Al this aircraft in od IAW FAR and was determined was determined to condition.	NA 421C S/ iz 7514.) Annual inspense work Jack ne replaced by ed nose strut, vacuum reguli s noted. Para- rected ELT IA 2016-07-24 nov inspection due, lastalled overhit stack rest on MIOJS35IA. () as 43 App (d) an	CAPE GRANDEAU ARCHONAL ARRONG  CAPE GRANDEAU ARCHONG  N 421C0897 N617CC  Sixon IAW FAR 43 (App d) and labricated IAW service manual sed ascendt. Serviced blow down bottle with nitrogen. Service drauble filters. Packed all wheel bearings and replaced nose wheel Performed retraction test operation normal. Removed arreraft stor filters P/N B3-5-9. CW AD2000-01-16 rev. 2-15-2000 IAW (b) due again at hobbs 7564.1 para (c) February 2022, para (e) due W FAR91-207 (d) 1-4 eaxt inspection due February 2022.  4-25-16 by inspection of elevator trim tab actuator attachment and attachment indicator on left instrument panel P/N102-004 I de pilot armiest. Replaced bonding strap to midder. Installed new Replaced instrument panel P/N102-004 II.	

age No.		
Hobbs 7571.5	ed aircraft and installed new tires and tubes. Removed aircraft from jacks. Replaced (	O-rings in
Hobbs 7579.8 Tot On this date complet performed the follow Service brake and hy operation normal R CW AD2000-01-16: para (c) September 2 inspection due Febru actuator attachment I Throttle and mixture 10B38.0 pressurizatio I certify that this airc	ted an Annual inspection IAW FAR 43 (App d) and lubricated IAW service manual article and Annual inspection IAW FAR 43 (App d) and lubricated IAW service manual article with mitrogen. Serviced O2 Boydraulic systems replaced hydraulic filters. Packed all wheel bearings. Performed retriemoved aircraft from jacks. Installed new vacuum regulator filters P/N B3-5-9. rev. 2-15-2000 IAW para (b), (c), (e) no defects noted. Para. (b) due again at hobbs 7023, para (e) due again September 2023. Inspected ELT IAW FAR91.207 (d) 1-4 neuroper 2022. Serviced O2 system. AD2016-07-24 rev 4-26-16 by inspection of elevated IAW MEB-27-02. Next inspection due September 2023 or hobbs 7689.8. Installed new Called the cables on left side using new P/N1220-37 and 1220-39 and rigged. Installed new Called the Called the Called IAW App (d) an Annual letermined to be	ottle. raction test 7629.8 xt or trim tab
Hobbs 7605.3	OZARK AIRCRAFT MAINTENANCE LLC  CAPE GIRARDEAU REGIONAL AIRPORT  CAPE GIRARDEAU MO 63701  CESSNA 421C S/N 421C0897 N617CC  Total Time 7605.3  new battery P/N 7246-20. Replaced aft door cable P/N 51-00  S/A G03135262	